AMENDMENT TO THE CLAIMS

The following claim set replaces all prior versions, and listings, of claims in the application:

1.-12. (canceled)

- 13. (currently amended) High-performance polyethylene multifilament yarn comprising made from linear ultra-high molar mass polyethylene of IV 8-40 dl/g, containing n filaments and having a tensile strength of at least f *(n^{-0.065}) GPa, wherein factor f is at least 5.8 and n is at least 5, and wherein the filaments are made from linear ultra-high molar mass polyethylene of IV 8-40 dl/g as measured on solutions in decalin at 135°C.
- 14. (original) High-performance polyethylene multifilament yarn according to claim 13 wherein f has a value from 6.0 to 10.
- 15. (previously presented) High-performance polyethylene multifilament yarn according to claim 13, showing a non-reversible peak, as measured by temperature-modulated differential scanning calorimetry, with a maximum at about 152°C and having an enthalpy of at least 35 J/g.
- 16. (previously presented) High-performance polyethylene multifilament yarn according to claim 13, having a creep rate as determined on yarn at 70°C with a load of 600 MPa of at most 5 * 10⁻⁶ s⁻¹.
- 17. (previously presented) High-performance polyethylene multifilament yarn according to claim 13, containing at least 200 filaments.
- 18. (currently amended) High-performance polyethylene multifilament yarn according to claim 13, wherein the filaments are solution spun, and wherein the

SIMMELINK et al Serial No. 10/584,285 April 22, 2009

<u>filaments contain</u> <u>eentaining</u> less than 150 ppm of residual <u>spinning</u> solvent <u>of a type</u> having a boiling point at atmospheric conditions of less than 275°C.

19. (previously presented) Semi-finished and end-use articles containing the high-performance polyethylene multi-filament yarn according to claim 13.

20.-25. (Canceled)